

Creating a **CUPS** Backend

Adam Tauno Williams
awilliam@whitemice.org
GPG D95ED383

Copyright

© 2014 Adam Tauno Williams (awilliam@whitemice.org)

CUPS

Common UNIX Printing System

If you have printed using LINUX or Mac OS/X you have used CUPS.

<http://www.cups.org/>

Backends

The options you see when you add a printer.

Add Printer

- Local Printers:** ☐ SCSI Printer
☐ Serial Port #1
☐ Serial Port #2

- Discovered Network Printers:** ☐ TASKalfa 5500i (Kyocera TASKalfa 5500i)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ hp LaserJet 4200 (HP LaserJet 4200)
☐ hp LaserJet 4200 (HP LaserJet 4200)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ FS-C2626MFP (Kyocera FS-C2626MFP)

- Other Network Printers:** ☐ Internet Printing Protocol (ipp)
☐ AppSocket/HP JetDirect
☐ Windows Printer via SAMBA
☐ Internet Printing Protocol (http)
☐ Backend Error Handler
☐ LPD/LPR Host or Printer
☐ Internet Printing Protocol (https)

Why Create A Backend?

- Because everything can print!
 - This is a simple way to get data/documents into an application from any arbitrary thing.
 - Go paperless!
- Modify print jobs

You



Client/User



"Prints"




to the server.

*converts
to PDF?*



*does
something*

Example



List Backends

```
linux-86wr:/home/awilliam # lpinfo -v  
network http  
network ipp  
network ipp  
network https  
direct hp  
network socket  
network lpd  
network smb  
direct hpfax  
network beh
```

Add Printer

Local Printers: ☐ SCSI Printer
☐ Serial Port #1
☐ Serial Port #2

Discovered Network Printers: ☐ TASKalfa 5500i (Kyocera TASKalfa 5500i)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ hp LaserJet 4200 (HP LaserJet 4200)
☐ hp LaserJet 4200 (HP LaserJet 4200)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ FS-C2626MFP (Kyocera FS-C2626MFP)

Other Network Printers: ☐ Internet Printing Protocol (ipp)
☐ AppSocket/HP JetDirect
☐ Windows Printer via SAMBA
☐ Internet Printing Protocol (http)
☐ Backend Error Handler
☐ LPD/LPR Host or Printer
☐ Internet Printing Protocol (https)

What are these?

```
> ls -l /usr/lib/cups/backend/  
total 324  
-rwxr-xr-x 1 root root 7250 Sep 21 2013 beh  
-rwxr-xr-x 1 root root 18976 Jan 15 2014 hp  
-rwx----- 1 root root 9067 Jan 15 2014 hpfax  
lrwxrwxrwx 1 root root 3 Mar 29 22:15 http -> ipp  
lrwxrwxrwx 1 root root 3 Mar 29 22:15 https -> ipp  
-rwx----- 1 root root 68912 Mar 4 04:46 ipp  
lrwxrwxrwx 1 root root 3 Mar 29 22:15 ippes -> ipp  
-rwx----- 1 root root 43928 Mar 4 04:46 lpd  
-r-xr-xr-x 1 root root 35640 Mar 4 04:46 parallel  
-r-xr-xr-x 1 root root 35624 Mar 4 04:46 serial  
lrwxrwxrwx 1 root root 17 Mar 29 22:16 smb -> /usr/bin/smbpool  
-r-xr-xr-x 1 root root 27368 Mar 4 04:46 snmp  
-r-xr-xr-x 1 root root 35616 Mar 4 04:46 socket  
-r-xr-xr-x 1 root root 35624 Mar 4 04:46 usb
```

Backends with world-execute run as the CUPS user,
otherwise backends run as root.

Enumeration

- Called with no arguments
 - When you did `lpinfo -v`
 - Add a printer in the web UI.

if len(argv) > 5:

....

else:

```
    print('network cups-to-ogo '
```

```
        "\"Generic Postscript Printer Foomatic/Postscript (en)\" '
```

```
        "\"OpenGroupware\"")
```

```
sys.exit(0)
```

- Output a whitespace delimited string describing the backend.
- Exit with a status of 0

Description

type backend-name default-printer-type display-name

- **type** = network, this is 2014
- **backend** = Backend name, the name of the script.
- **default-printer-type** – The rendering type of the printer.
- **display-name** = Display name for the administrator of the backend.

White-space separated values – so if your values contain whitespace they need to be quoted.

```
print(  
  'network cups-to-ogo '  
  "\"Generic Postscript Printer Foomatic/Postscript (en)\""  
  "\"OpenGroupware\""  
)
```

Now you see it.

Add Printer

Local Printers: ☐ SCSI Printer
☐ Serial Port #1
☐ Serial Port #2

Discovered Network Printers: ☐ TASKalfa 5500i (Kyocera TASKalfa 5500i)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ hp LaserJet 4200 (HP LaserJet 4200)
☐ hp LaserJet 4200 (HP LaserJet 4200)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ TASKalfa 2550ci (Kyocera TASKalfa 2550ci)
☐ FS-C2626MFP (Kyocera FS-C2626MFP)

Other Network Printers: ☐ Internet Printing Protocol (ipp)
☐ AppSocket/HP JetDirect
☐ Windows Printer via SAMBA
☐ Internet Printing Protocol (http)
☐ Backend Error Handler
☐ LPD/LPR Host or Printer
☐ Internet Printing Protocol (https)
☒ OpenGroupware (Generic Postscript Printer Foomatic/Postscript (en))

Continue

You can create a printer

Add Printer

Connection:

Examples:

`http://hostname:631/ipp/`
`http://hostname:631/ipp/port1`

ogo_mailback (Idle, Accepting Jobs, Shared)

Maintenance

Administration

Description: Submit to MailBack Workflow

Location: MorCloud

Driver: Generic PostScript Printer Foomatic/Postscript (recommended) (color, 2-sided printing)

Connection: cups-to-ogo://dav/Workflow/Routes/TEST_MailBack/input?subject=\${title}

Defaults: job-sheets=none, none media=na_letter_8.5x11in sides=one-sided

Jobs

But how does it do stuff?

```
if len(argv) > 5:  
    job_id = argv[1]  
    user_id = argv[2]  
    title = argv[3]  
    copies = argv[4]  
    options = argv[5]  
    if len(argv) == 7:  
        filename = argv[6]  
    else:  
        filename = None  
else:
```

If you get command arguments then it is a print job.

- If you have a seventh argument it is the file containing the job.
- If there is no filename then the data is coming in on standard-in.
 - This is what always happens.

Parameters?

CUPS pushes the queue's configured URI, including the backend prefix, into the processes environment.

```
device_uri = os.getenv('DEVICE_URI')
```

```
cups-to-ogo://dav/Workflow/Routes/TEST_MailBack/input?subject=${title}
```

Use of any any innumerable URI/URL parsing libraries.

```
pu = urlparse.urlparse(device_uri)
```

Standard In

Most of the time your job data will arrive via standard in; it is recommended to read this into a temporary file prior to processing.

```
rfile = TemporaryFile()  
shutil.copyfileobj(sys.stdin, rfile)  
rfile.seek(0)  
do some stuff  
rfile.close()
```

Response

- Status of job is exit code of backend:
 - 0 – Success / Complete
 - 1 – Failed
 - 2 – Authentication Required
 - 3 – Hold
 - 4 – Stop
 - 5 – Cancel
 - 6 – Retry

For Example

```
response = connection.getresponse()
syslog.syslog(
    syslog.LOG_INFO,
    'HTTP Result: {0}'.format(response.status, )
)
result = 1 # Backend failed, generic
if response.status in (200, 201, 202, 204, 301, ):
    result = 0 # Backend success
elif response.status in (401, 419, 511, 496, 496, ):
    result = 2 # Authentication Failed
elif response.status in (423, 409, 408, 429, ):
    result = 6 # Retry
elif response.status in (418, 451, ):
    result = 5 # Cancel Job, Teapot or illegal response
connection.close()
return result
```